

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-206339

(43)Date of publication of application : 28.07.1992

1)Int.Cl.

H01M 2/12

1)Application number : 02-330246

(71)Applicant : TOSHIBA BATTERY CO LTD

2)Date of filing : 30.11.1990

(72)Inventor : ITO YUKIHIRO


IIZUKA KAZUO

4) ALKALI DRY CELL

7)Abstract:

PURPOSE: To obtain a satisfactory leak resisting property by covering the gas discharge hole part of a negative electrode terminal plate with a thermally melting material softened and melted at a specified temperature.

CONSTITUTION: A negative electrode terminal plate 8 is placed on the stepped part 54 of an insulating gasket 5 provided on the opening part of a metal can 1 through a ring metal support body 7 having an air hole 7a, and the gas discharge hole part 8a of the negative electrode terminal plate 8 is covered with a thermally melting material softened and melted at 70-90°C. A coat layer 9 of paraffin wax having a melting point of 75°C, for example, as the thermally melting material is formed. Thus, the leak passage of the electrolyte climbed up along a collecting bar 6 and moved along the inner surface of the negative electrode terminal plate 8 can be cut by the paraffin wax coat layer 9. Thus, a satisfactory leak resisting characteristic can be obtained.



GAL STATUS

Date of request for examination]

Date of sending the examiner's decision of rejection]

Kind of final disposal of application other than the

examiner's decision of rejection or application

converted registration]

Date of final disposal for application]

Patent number]


Date of registration]

Number of appeal against examiner's decision of
ejection]

Date of requesting appeal against examiner's
ecision of rejection]

Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office



The Delphion
Integrated
View

Other Views:
[INPADOC](#)

Title: **JP4206339A2: ALKALI DRY CELL**

► [Want to see a more descriptive title highlighting what's new about this invention?](#)

Country: **JP** Japan
Kind: **A**

Inventor(s): **ITO YUKIHIRO**
IIZUKA KAZUO

Applicant/Assignee:



TOSHIBA BATTERY CO LTD

[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **July 28, 1992 / Nov. 30, 1990**

Application Number: **JP1990000330246**

IPC Class: **H01M 2/12;**

Priority Number(s): Nov. 30, 1990 **JP1990000330246**

Abstract:



Purpose: To obtain a satisfactory leak resisting property by covering the gas discharge hole part of a negative electrode terminal plate with a thermally melting material softened and melted at a specified temperature.

Constitution: A negative electrode terminal plate 8 is placed on the stepped part 54 of an insulating gasket 5 provided on the opening part of a metal can 1 through a ring metal support body 7 having an air hole 7a, and the gas discharge hole part 8a of the negative electrode terminal plate 8 is covered with a thermally melting material softened and melted at 70-90°C. A coat layer 9 of paraffin wax having a melting point of 75°C, for example, as the thermally melting material is formed. Thus, the leak passage of the electrolyte climbed up along a collecting bar 6 and moved along the inner surface of the negative electrode terminal plate 8 can be cut by the paraffin wax coat layer 9. Thus, a satisfactory leak resisting characteristic can be obtained.


COPYRIGHT: (C)1992,JPO&Japio

► [See a clear and precise summary of the whole patent, in understandable terms.](#)

Family: [Show known family members](#)

Other Abstract Info: DERABS C92-296804 DERC92-296804


Foreign References: No patents reference this one



[View Image](#)

1 page





**Nominate this
for the Gallery...**

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.